



## PRODUCT SPECIFICATIONS

Detail Photos  
*(on right from top to bottom)*  
Subreflector de-icer  
Feed horn heater (optional)  
Moisture-temperature sensor



De-icing unit available for dual optics subreflector and feed horn. De-icing units are also available for other feed horns as an option.

## Active De-Icing System

The Andrew Corporation Active De-Icing System is custom designed for our line of VSAT RxTx antenna systems.

A de-icing system prevents signal loss due to snow and ice build-up on the surface of the reflector.

The Andrew Corporation half-aperture reflector de-icing system consists of a defrost panel that is attached to the reflector by self-drilling screws.

The Andrew Corporation De-Icing system can easily be installed in the field using a socket wrench and cordless drill. Removal of two lower reflector bolts is necessary to install the defrost panel.

Moisture and temperature sensors allow the system to activate when temperatures are below 38° F and when precipitation exists. Heating elements supply heat uniformly over the surface of the defrost panel, which consists of the following three layers:

- The outside layer is a heavy-duty, vinyl-coated polyester material that is especially designed for weather protection.
- The middle layer consists of high temperature insulation.
- The inside layer, next to the rear, lower half of the reflector, contains the heating elements.

**SPECIFICATIONS**

**ACTIVE DE-ICING SYSTEM**

The Andrew Corporation De-Icing System is lightweight and can be shipped via UPS. Models are available for the 96cm, 1.2m, 1.8m and 2.4m offset reflectors. Models are available in 120v or 240v. Special models are available for 1.8m and 2.4m dual optics antennas. An optional Ku-Band feed horn heater is available in 120v or 240v for all de-icer models.

<b>Antenna Size</b>	<b>Model</b>			
96cm .....	6321			
1.2m .....	6322			
1.8m .....	6323			
2.4m .....	6324			
<b>Description</b> .....	Half-Aperture Reflector De-Icing System for Andrew Corporation 96cm, 1.2m, 1.8m and 2.4m Offset Antennas.			
<b>Circuit Requirements</b> .....	<b>96cm</b>	<b>1.2m</b>	<b>1.8m</b>	<b>2.4m</b>
<b>120 VAC</b>	3.5A	4A	8A	15A
<b>240 VAC</b>	1.8A	2A	4A	8A
<b>Power Consumption</b> .....	400 W	500 W	1000 W	1800 W
<b>Sensor</b> .....	Moisture/Temperature			
<b>Operation</b> .....	Heaters operate when temperature is below 38°F and moisture is present. System remains on for one hour thereafter. Low temperature lockout disables heaters below 17°F when snow rarely forms.			
<b>Smart Bypass Switch</b> .....	This switch allows for manual operation during installation or for testing purposes. If left on, it reverts to automatic mode after 40 hours.			



Andrew Corporation  
10500 W. 153rd Street  
Orland Park, IL 60462 USA

One Company. A World of Solutions.

**Customer Support Center**  
From North America  
Telephone: 1-800-255-1479  
Fax: 1-800-349-5444  
satcom@andrew.com

**International**  
Telephone: +1-708-873-2307  
Fax: +1-708-349-5444

**Internet:** www.andrew.com

All designs, specifications and availabilities of products and services presented in this bulletin are subject to change without notice.

Bulletin 11053 (2/05)  
© 2005 Andrew Corporation, Orland Park, IL 60462 USA